

Biocides free and weather resistant blend of plant oils for exterior and interior wood protection.

INGREDIENTS

Linseed oil, Wood oil, Gum turpentine, essential oils, lead-free driers and pigments of natural occurrence or non-toxic mineral pigments. *Natural paints are not odour and emission free and may cause allergies. Always provide for good ventilation!*

AREA OF USE

For the water repellent and durable treatment of all exterior and interior timber. Does not contain any biocides.

COLOURS AVAILABLE

Clear (slightly yellow), chestnut, imbuia. *Other colours are available on request.*

ProNature Outdoor clear is only slightly UV-stabilized and thus less durable than colours like chestnut or imbuia. Shorter renovation intervals are to be expected.

COVERAGE

Approximately 10 m²/liter/per application

Coverage is much lower when applied to roughly sanded surfaces.

SURFACE PREPARATION

Clean surface and sand wood to a very fine, smooth finish using grit i.e. 100, preferably finer 180 or higher. Surface must be dry, clean and dust-free.

If the wood is subject to attack by insects or fungi pre-treatment with **ProNature Timber Watch** is recommended (see separate datasheet).

APPLICATION *untreated wood*

Stir material well before application. **ProNature Outdoor** is applied liberally using a brush or dip application. Where suitable material can also be sprayed. In order to avoid glossy spots and prolonged drying it is necessary to remove any excess that has not been absorbed after about 10 min using a lint-free cloth. Leave to dry for a minimum 6 hrs.

A light sanding after drying is recommended if necessary. Then apply second coat of **ProNature Outdoor** following above instructions. Allow drying for a minimum of 6 hrs.

Again a very light sanding is recommended if necessary before applying the final coat following above instructions.

Only surfaces, which are subject to extreme weather conditions, should receive an additional coating after a 24 hr drying period.

For interior use an application of two to three coats is adequate.

! Cold weather and high humidity will retard the drying!!!

APPLICATION *previous coated wood*

Remove all previous coatings by means of sanding or suitable paint stripper. Sand to a very fine, smooth finish. Any wood defects like deterioration by fungi or insects must be removed and a pre-treatment with **ProNature Timber Watch** may be required. After pre-treatment follow above instructions for untreated wood.

GENERAL INFORMATION:

ProNature Outdoor is ready to use and needs not be diluted. Depending on the wood type a thinning down of the first coat with about 10 % of **ProNature Plant Turpentine** is recommended. Clean tools with **ProNature Plant Turpentine**.

ProNature Outdoor should be applied in regular intervals at least once a year or whenever necessary.

SAFETY PRECAUTIONS

Caution: Product is ignitable! Soaked, used cloths may spontaneously combust, and should be spread open, or kept safely in a tightly sealed tin after use.

PACKAGE SIZES

1 l, 5 l and 25 l

STORAGE STABILITY

A minimum of 6 months in unopened containers when stored in a cool and dry place.

General

The above information given is intended as a guideline only. Since this product is used outside of our control, EnviroTouch CC cannot be held liable for any loss or damage whatsoever relating to the application or surface it is applied to. We reserve the right to change specifications at any time and without prior notice.

Last revised: 2/2007