



ProNature Teak Cleaner and Teak Reviver

INGREDIENTS

Water, Potassium soaps, Fruit acids, Mineral Acids

AREAS OF USE

For the cleaning and restoring of weathered (grey) teak and other wood types.

SURFACE PREPARATION

Clean surface of loose dirt, algae etc. by scrubbing with a stiff bristle brush.

CONSUMPTION

Depending on the state of ageing of the wood approx. 10 - 15 m²/litre, on non-porous, flat substrate.

APPLICATION

Moisten wood. Using a sponge or cloth apply liberal amounts **ProNature Teak Cleaner**. Allow the cleaner to draw in for about 2-3 minutes before scrubbing in direction of the wood grain using a stiff short-bristle brush or scrubbing pad. Thoroughly rinse wood with clean water, easily done using a jet of water from a hosepipe. Severely dirty or weathered wood may require a second treatment until wood shows its natural colour and grain.

If sanding is required this should be done before application of **ProNature Teak Reviver**.

Allow the wood to dry lightly before applying a liberal amount of ProNature Teak Reviver using a brush or sponge (the use of rubber gloves is recommended). Leave to penetrate for at least 5 minutes and then rinse thoroughly with clean water. This will restore the original wood colour.

Clean tools with water.

Note: Immediately rinse off spills from surfaces not treated.

For proper protection coat the wood using **ProNature Outdoor**. See separate leaflet.

ProNature Teak Cleaner is also suitable for the cleaning of oiled and waxed surfaces i.e. finished with ProNature Floor or ProNature Wax Balm etc.

For cleaning of wooden floors dilute **ProNature Teak Cleaner** 1:5 with water. If dirt is very stubborn used undiluted.

STORAGE

Store in a cool and frost-free place.

PACKAGE SIZES

0,5l, 1l, 5l, or as Teak Set which contains 200 ml **ProNature Teak Cleaner**, 200 ml **ProNature Reviver** + scrubbing pad + instructions.

General

The above information given is intended as a guideline only. Since this product is used outside of our control, EnviroTouch CC cannot be held liable for any loss or damage whatsoever relating to the application or surface it is applied to. We reserve the right to change specifications at any time and without prior notice.

Last revised: **9/2003**