



Pro *Nature*

Care Oil

Truly Eco-Friendly
Wall Paints,
Cleaning Products
Wood & Stone Finishes.

Locally Produced
Natural & Sustainable
Truly Eco-Friendly!



Tel: 0860 105 299
www.pronature.co.za

Blend of plant oils and gum rosin for the protection of wooden surfaces.

INGREDIENTS

Linseed oil, gum rosin, plant oils, essential oils, lead-free driers.

Note: Natural products are not odour and emission free. Consider possible allergies!

TVOC (total volatile organic content) = 723.44 g/litre

AREAS OF USE

For the periodic maintenance of wooden surfaces treated with **ProNature Floor** or **ProNature Indoor**. Also suitable for previously varnished wooden floors, provided they were not waxed. Wax residues must be stripped completely before applying **ProNature Care Oil** using **ProNature Plant Turpentine** or any other suitable wax stripper. **ProNature Care Oil** will maintain the wood moisture balance of previously oiled surfaces ("wood can breathe") and such creates a pleasant room climate.

GENERAL

For reasons of environmental safeness and ease of restoration wooden surfaces should not be "sealed". Even though the hardness of two component synthetic coatings can not be achieved with natural coatings, synthetic coatings are also not entirely safe from scratching and wear and can only be repaired by complete removal and recoating.

Natural coatings have the added advantage not to contain any ingredients, which could cause harmful emissions, like formaldehyde or aromatic solvents, which could have a negative health impact.

COVERAGE

Approximately 50 – 100 m²/litre, depending on type of wood and degree of soiling.

SURFACE PREPARATION

Remove grit, dust and other loose dirt. Clean the surfaces with a neutral soap solution and well wrung out scouring cloth. Alternatively, a cleaning machine with the least amount of water possible may be used.

Wipe dry immediately.

APPLICATION

Moisten cloth with **ProNature Care Oil** and apply sparingly until the whole surface is covered. Alternatively, can the material be applied securing the moist cloth to a dry circular pad of a surfaces polisher (150 rpm). Continuously add more **ProNature Care Oil** so that the entire surface is covered with oil. In order to avoid glossy spots and prolonged drying it is important to remove and dry off any excess that has not been absorbed thoroughly after about 15 min using a lint-free cloth or a surfaces polishing machine (soft pad). Leave to dry for 1-2 hours and then dry polish with soft pad or lint-free cloth in direction of the grain (300 rpm). Allow drying for a minimum of 12 hrs. Should a second coat be desired repeat above described procedure.

If the surface is very soiled the first application of **ProNature Care Oil** should be more liberal approx. 1 litre to 15 m². Then work crosswise with a red or green pad (150 rpm) removing all stubborn dirt. Remove surplus after about 15 min using a lint-free cloth or a surfaces-polishing machine (soft pad) and then continue as described above. The best results are achieved if the surface is left unused for 12 hours. However, the surfaces can be used and walked on after only 2-3 hours.

CLEANING, CARE and REPAIR

The durability of an oiled wooden surface highly depends on regular cleaning and care. For the first two weeks' surfaces should not be cleaned wet but only swept. Thereafter surfaces are cleaned with **ProNature Plant Soap** and wiped with a damp cloth only. *Avoid any standing water!!!*

ProNature Care Oil should be applied in regular intervals i.e. three times a year or when necessary. Apply sparingly and polish after a drying time of approx. 1hr.

GENERAL INFORMATION:

ProNature Care Oil is ready to use and needs not be diluted. Clean equipment with **ProNature Plant Turpentine**.

SAFETY PRECAUTIONS

Caution: Product is inflammable! Soaked, used cloths may spontaneously combust, and should be spread open, or kept safely in a tightly sealed tin after use.

PACKAGE SIZES

0.5 l, 1 l, 5 l and 25 l

STORAGE STABILITY

A minimum of 12 months in unopened containers when stored in a cool and dry place.

General

The above information given is intended as a guideline only. Since this product is used outside of our control, EnviroTouch CC cannot be held liable for any loss or damage whatsoever relating to the application or surface it is applied to. We reserve the right to change specifications at any time and without prior notice.

Last revised: 04/2016