



# **Pro** *Nature*

## *Mould Stop*

Truly Eco-Friendly  
Wall Paints,  
Cleaning Products  
Wood & Stone Finishes.

Locally Produced  
Natural & Sustainable  
Truly Eco-Friendly!



**Tel: 0860 105 299**  
**[www.pronature.co.za](http://www.pronature.co.za)**

## INGREDIENTS

Water, citric acid, hydrogen peroxide, alcohol, sugar surfactant

Note: Natural products are not odour and emission free. Consider possible allergies!

## AREA OF USE

Destroys mould, mould spores (mycotoxins) and bacteria. Preserves the substrate within minutes and prevents re-infestation.

## COVERAGE

Approximately 9 – 14 m<sup>2</sup>/litre, depending on substrate.

## APPLICATION

Apply with suitable spraying equipment, brush or sponge to the affected areas and allow a residence time of approx. 60 minutes, longer in case of severe infestation. Then wipe off residual mould or rinse off with water.

Please check surface compatibility in an inconspicuous area prior to use.

Wash tools with water directly after use. Do not store in metal containers!

## SAFETY PRECAUTIONS

**Caution:** Mycotoxins are a health risk and the following precautionary measures should be followed: Wear a dust mask to avoid breathing in mould and spores. Wear gloves to avoid skin contact.

Avoid skin and eye contact with ProNature Mould stop. After contact with skin, wash immediately with plenty of water.

**Keep** ProNature Mould Stop **away from children**. When swallowed seek immediate medical attention and show product label to medical practitioner.

## PACKAGE SIZES

1 l, 5 l and 25 l

## STORAGE/SHELF LIFE

The product can be kept for a minimum of 12 months in unopened containers when stored in a cool (but frost-free) and dry place.

Tips for mould prevention:

- Keep the relative air humidity at approx. 50 %.
- Keep temperature in all rooms equal, the temperature difference between individual rooms should not exceed 5 °C.
- Keep doors to cooler rooms closed, e.g. to unheated bedrooms, in order to prevent warm and thus damp air from the other rooms from condensing on the walls.
- Cross ventilate rooms 3-4 times a day
- Use technical appliances (controlled ventilation systems).
- Discharge moisture from showering or cooking to the outside immediately.
- Do not dry laundry in the flat.
- Leave at least 5 cm distance between furniture and outer walls.
- Use vapour permeable construction materials and wall coatings, e.g. all products from the ProNature paint range.
- Find cold bridges: Insufficiently insulated structural components cool down the inner walls, where air humidity then condenses.

## General

The above information given is intended as a guideline only. Since this product is used outside of our control, EnviroTouch CC cannot be held liable for any loss or damage whatsoever relating to the application or surface it is applied to. We reserve the right to change specifications at any time and without prior notice.

Last revised: 07/2011