



Pro *Nature*

Wax Balm

Truly Eco-Friendly
Wall Paints,
Cleaning Products
Wood & Stone Finishes.

Locally Produced
Natural & Sustainable
Truly Eco-Friendly!



Tel: 0860 105 299
www.pronature.co.za

ProNature Wax Balm is a pleasant smelling paste, comprising natural oil and waxes. It penetrates deeply and beautifies the grain of the wood.

INGREDIENTS

Linseed Oil, Beeswax, Carnauba wax, Essential Oils.

Note: Natural products are not odour and emission free. Consider possible allergies!

TVOC (total volatile organic content) = 600.62 g/litre

AREAS OF USE

For the universal treatment of furniture, toys, wooden ceilings, wall panelling, as well as wooden floors or mineral substrates like slate, stone tops etc. and for the periodic maintenance of wooden floors treated with **ProNature Floor** or with **ProNature Wax Balm** only.

COVERAGE

Approximately 0,020 l/m², depending on wood type.

SURFACE PREPARATION

Clean surface and sand wood to a fine, smooth finish using grit i.e.150-180, preferably finer. Surface must be dry, clean and dust-free.

APPLICATION

Depending on the surface, apply 1 – 2 coats of **ProNature Wax Balm** using a soft, lint-free cloth. Remove surplus with a clean piece of soft cloth, and polish the surface thoroughly.

If a higher quality finish is desired, apply an additional coat after drying.

The final hardness of the finish is only reached after a few days of drying. When applied to wooden floors, treat the floors during this period carefully and avoid the engraining of dirt.

Maintenance of oiled/waxed Floors

Remove grit, dust and other loose dirt. Clean the floor with a neutral soap solution and well wrung out scouring cloth. Alternatively, a cleaning machine with the least amount of water possible may be used.

Wipe dry immediately. Moisten cloth with **ProNature Wax Balm** and apply **sparingly** until the whole floor is covered. Alternatively apply the **ProNature Wax Balm** using a polishing pad of a floor polishing machine. It is important to apply as little **ProNature Wax Balm** as possible. Remove surplus with a clean piece of soft cloth or polishing pad and polish the surface thoroughly. Polishing should commence not earlier than an hour after applying ProNature Wax Balm and higher sheen is acquired by allowing ProNature Wax Balm to set for a couple of hours.

A strict maintenance routine should be established of at least three times per year or whenever necessary. It is important to remove all excess wax thoroughly!

GENERAL INFORMATION:

ProNature Wax Balm is ready to use and needs not be diluted. Clean brushes and equipment with **ProNature Plant Turpentine**.

SAFETY PRECAUTIONS

 Product is ignitable! No danger of spontaneous combustion.

PACKAGE SIZES

0.5 l, 1 l, 5 l and 25 l

STORAGE STABILITY

A minimum of 12 months in unopened containers when stored in a cool and dry place.

PRODUCT CODE: 103

General

The above information given is intended as a guideline only. Since this product is used outside of our control, EnviroTouch CC cannot be held responsible for any loss or damage whatsoever relating to the application or surface it is applied to. We reserve the right to change specifications at any time and without prior notice.

Last revised: 4/2016