

**Product Description:**

A blend of plant oils to protect, impregnate and optionally tint wood. Can be used on all interior timber, including floors, as well as all wooden furniture (Tables, chairs, desks, cupboards, bed frames etc).

ProNature Indoor is food safe and can be used on cutting boards, toys, worktops, kitchen counters and more.

Ingredients:

Linseed oil, blend of vegetable oils, lead-free driers, natural and non-toxic mineral pigments.

TVOC (total volatile organic content) = 22.07 g/litre

Colours:

Please refer to our extensive colour range. We do offer customized colours.

Coverage:

Approximately 20-30 m² per single application, depending on the type of wood.

For optimum durability apply 3 coats.

Application:

Watch this short video! <https://www.pronature.co.za/tips-tricks/>

Product is ready to use. Do not dilute.

Surface must be dry, clean and dust-free. Sand wood to a fine, smooth finish using min grit 100.

- ✓ Stir well!
- ✓ Apply liberally using brush or short bristle paint roller (or wipe with cloth) until saturation is reached.
- ✓ Remove and dry off any excess thoroughly that has not been absorbed after **about 10 min** using a lint-free cloth i.e. **ProNature Mutton Cloth**.
- ✓ Leave to dry for a minimum of 6 hours and if necessary lightly sand the surface before applying the next coat.
- ✓ The finish will take about 7 days to fully cure, avoid standing water during this period.

NB: Cold weather and/or high humidity will prolong the drying process.

Caution:

Product is ignitable! Soaked, used cloths may spontaneously combust, and should be spread open, or kept safely in a tightly sealed tin or best to be submersed in water after use.

Cleaning:

Use **ProNature Plant Turpentine** for brushes & rollers. Use **ProNature Plant Soap Concentrate** for severe stains and prior to re-oiling.

General Maintenance, Care & Repair:

Use **ProNature Wood Cleaner** for all wooden surfaces.

Re-apply ProNature Indoor once surface appears dry and lustreless. Repair: you can spot repair. Sand damaged area and apply ProNature Indoor. It will blend in once the product has fully cured.

Storage/Shelf life:

Store in a cool, dry place. Minimum stability 12 month in closed container.

Disposal:

Oil based paint must be taken to a hazardous landfill site or other municipal collection points. DO NOT empty this oil based liquid residue into drains.

Safety:

Natural ingredients may cause allergies. Use only as directed. Keep out of reach of children. Supervise children during use.

General:

The above information given is intended as a guideline only. Since this product is used outside of our control, ProNature cannot be held liable for any loss or damage whatsoever relating to the application or surface it is applied to. We reserve the right to change specifications at any time and without prior notice.

Maintenance

Maintenance Schedules and Recommendations for wooden surfaces

In order to keep timber in its original colour and to avoid degradation through the elements it is necessary to do **REGULAR** maintenance. As always proper preparation is the key to success. Please follow the following instructions and recommendations to ensure long life of your wooden surfaces.

Surface preparation:

Prior to applying ProNature Indoor the timber should be prepared by ensuring it is clean and free of grease. Cleaning is made easy with the help of **ProNature Plant Soap Concentrate**. Sand to a smooth and even finish (insufficient sanding will be highlighted especially when sealing with a darker colour) if necessary.

Application:

Stir material well before application. For maintenance **ProNature Indoor (choose same colour as was used for the original coating)** is applied liberally using a brush or roller. In order to avoid glossy spots and prolonged drying it is necessary to remove any excess thoroughly that has not been absorbed after about 10 min using a lint-free cloth. Leave to dry for a minimum 6 hrs.

Only surfaces, which are subject to extreme weather conditions, should receive an additional coating after a 24 hr drying period.

In general, it is adequate to apply a single coat of **ProNature Indoor** for maintenance purposes. More coats may become necessary if maintenance had been neglected and the original coating has completely deteriorated. In this case it is recommended to re-apply ProNature as described in our technical data sheet or on the product container.

Maintenance Intervals:

It is recommended to regularly check all surfaces for deterioration of the oiled surfaces especially within the first year after application.

Have defaults become visible maintenance should commence immediately to avoid further damage.

It is recommended to have the first maintenance run within 6 months to a year after the original installation. Experience shows that this first maintenance run is the most important and extends the time to the next maintenance application substantially and re-coating is, depending on exposure, probably only necessary every two years.

We trust this information to be satisfactory. Should you, however, need further information please do not hesitate to contact the ProNature Team.